

IQ283

Hotel Guest Room Telephone

Feature List

- 6 year warranty
- Handsfree Speaker Phone
- Customised faceplate Insert
- 10 pre-programmable Guest Service Keys
- Message Waiting Light
- Available in Black or Ash
- Ringer pitch control
- Line powered
- Data port
- Recall key
- Redial key
- Ringer Light
- Mute key
- Ringer volume control
- Room number card Insert
- Permanent memory retention
- Electronics speaker volume control



Ash



Black

Brief Specifications of Interquartz IQ283	
Dial mode	Tone (DTMF)
Data Port	Shared mode standard, Optional split mode
10 Memory Buttons	32 digits each
Pause	Manual and Storable Pause of 1 second
PBXRecall	100 milliseconds Timed Break
Memory Retention	Non-volatile memory (permanent retention without power)
Power Source	Line powered. Batteries NOT required
Redial function	32 digits
Ringer Lamp	Superbright LED and Neon tube
Message Waiting light	Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index and Hybrex Optional: AT&T, Siemens ISDX, Siemens HICOM, Panasonic TD1232, Ericsson MD110 and some Hybrex
Dimensions	Width: 160mm; Length: 231mm; Height: 83.5mm
Ringer	Electronic, with Hi/Lo/Off settings; 80dBA at 1 Ft
Line cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall mount kit	Wall Mount Kit No.3 (Order separately)
Operating Temp and Humidity	Temperature : 0°C - 40°C; Humidity : 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Complies with AS/ACIF S004:2004. Instantaneous <123dB SPL, Continuous <120dBA)
Colour	Ash (L03) and Black (B3)