

## **Model IQ332**

### *Gemini Series Handsfree Telephone with Data Port*

#### Feature List

- Handsfree speakerphone with push button volume control
- Memory protection switch to allow pre-programming of memories
- 3 position ringer volume switch
- Tone dialling
- Mute key
- Recall key 100mS
- Redial and pause keys
- Alpha-numeric keypad
- Push button earpiece volume control
- Noise cancelling handset microphone
- Five (5) year parts and labour warranty
- Built-in message waiting and super bright LED ringer indicator lamp
- REN = 0.68 allows multiple parallel devices
- Data port in 'shared' mode – optional 'split'
- Screen printing available for hotel/company logo
- 10 memory keys (battery-free permanent storage)
- Acoustic shock protection for handset and headset
- Modular connection for installation on desk or wall
- Hearing aid compatible – hearing impaired and extra loud versions also available



<b>Brief Specifications of Interquartz IQ332</b>	
Dial Mode	Tone (DTMF)
Memory	10 Memory Keys
Pause	1 Second
PBX Recall	100 milliseconds Timed Break
Power Source	Line powered
Redial Function	32 digits
Ringer Lamp	Super bright LED and Neon tube
Message Waiting light	Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index, Hybrex, LG Aria Panasonic TD500 & TDA Series, Avaya 8700 & IP Office and Aristel 265 System with A4SLU card only Optional: AT&T, Siemens ISDX, Siemens Hicom, Ericsson MD110 and some Hybrex
Dimensions	Width: 160mm; Length: 230mm; Height: 60mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA at 30cm
Line Cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall Mount Kit	Wall Mount Kit No. 3 (order separately)
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Instantaneous – 90.3 dBA (ACA standard 123 dB SPL) Continuous – 114.3 dBA (ACA standard 120 dBA)
Colour	Black ABS plastic